


Aluminium Rundrohre

gepresst



Weitere Legierungen und Abmessungen gerne auf Anfrage!


EN-Nr.	AW 6060		
EN-Legierung	AlMgSi		
EN-Zustand	T66		
DIN-Nr.	3.3206		
DIN-Legierung	AlMgSi0,5		
DIN-Zustand	gepresst		
HL (mm) ca.	6.000		
Abmessung d x s (mm)	Abwickl. (mm)	Gewicht (~kg/m)	
6 x 1,0	18,85	0,05	○
8 x 1,0	25,13	0,06	●
x 1,5	25,13	0,09	●
10 x 1,0	31,42	0,08	●
x 1,5	31,42	0,12	○
x 2,0	31,42	0,14	●
12 x 1,0	37,70	0,10	●
x 1,5	37,70	0,14	●
x 2,0	37,70	0,17	●
x 3,0	37,70	0,24	○
13 x 1,5	40,84	0,16	●
14 x 2,0	43,98	0,21	○
x 2,5	43,98	0,26	○
15 x 1,0	47,12	0,13	●
x 2,0	47,12	0,24	●
16 x 1,0	50,27	0,15	●
x 1,5	50,27	0,19	●
x 2,0	50,27	0,24	●
18 x 1,5	56,55	0,22	●
x 2,0	56,55	0,28	●
x 3,0	56,55	0,34	●
20 x 1,0	62,83	0,17	○
x 1,5	62,83	0,25	●
x 2,0	62,83	0,32	●
x 3,0	62,83	0,43	●
x 4,0	62,83	0,57	○
x 5,0	62,83	0,67	●
22 x 1,0	69,12	0,20	●
x 1,5	69,12	0,27	●
x 2,0	69,12	0,36	●
24 x 1,5	75,40	0,29	○
x 2,0	75,40	0,38	○
25 x 1,0	78,54	0,22	●
x 1,5	78,54	0,32	○
x 2,0	78,54	0,37	●
x 2,5	78,54	0,50	●
x 3,0	78,54	0,59	●
x 4,0	78,54	0,75	●
x 5,0	78,54	0,85	●
28 x 1,0	87,96	0,23	○
x 1,5	87,96	0,36	○
x 2,0	87,96	0,46	●
x 2,5	87,96	0,57	○
x 5,0	87,96	1,03	○
30 x 2,0	94,25	0,45	●
x 2,5	94,25	0,59	●

EN-Nr.	AW 6060		
EN-Legierung	AlMgSi		
EN-Zustand	T66		
DIN-Nr.	3.3206		
DIN-Legierung	AlMgSi0,5		
DIN-Zustand	gepresst		
HL (mm) ca.	6.000		
Abmessung d x s (mm)	Abwickl. (mm)	Gewicht (~kg/m)	
30 x 3,0	94,25	0,69	●
x 4,0	94,25	0,92	●
x 5,0	94,25	1,06	●
32 x 2,0	100,53	0,54	●
x 3,0	100,53	0,78	●
34 x 4,0	106,81	1,13	○
35 x 2,0	109,96	0,56	●
x 2,5	109,96	0,69	○
x 3,0	109,96	0,86	○
x 5,0	109,96	1,37	●
38 x 1,5	119,38	0,46	●
x 2,0	119,38	0,64	○
x 3,0	119,38	0,96	●
x 5,0	119,38	1,55	○
40 x 1,5	125,66	0,52	○
x 2,0	125,66	0,67	●
x 2,5	125,66	0,85	○
x 3,0	125,66	0,99	●
x 4,0	125,66	1,28	●
x 5,0	125,66	1,57	●
x 6,0	125,66	1,73	○
x 8,0	125,66	2,32	●
x 10,0	125,66	2,72	●
42 x 2,0	131,95	0,71	●
42 x 3,0	131,95	0,99	○
45 x 2,0	141,37	0,78	●
x 2,5	141,37	0,95	●
x 3,0	141,37	1,12	○
x 5,0	141,37	1,79	●
x 8,0	141,37	2,69	●
48 x 3,0	150,80	1,20	●
x 4,0	150,80	1,51	●
50 x 2,0	157,08	0,81	●
x 2,5	157,08	1,06	●
x 3,0	157,08	1,20	●
x 4,0	157,08	1,67	●
x 5,0	157,08	1,96	●
x 10,0	157,08	3,62	●
55 x 2,0	172,79	0,90	●
x 2,5	172,79	1,17	●
x 5,0	172,79	2,12	●
60 x 2,0	188,50	1,00	●
x 2,5	188,50	1,28	●
x 3,0	188,50	1,61	●
x 4,0	188,50	2,03	●
x 5,0	188,50	2,34	●

○ = kurzfristig lieferbar ● = auf Lager

Aluminium Rundrohre

gepresst



EN-Nr.	AW 6060
EN-Legierung	AlMgSi
EN-Zustand	T66
DIN-Nr.	3.3206
DIN-Legierung	AlMgSi0,5
DIN-Zustand	gepresst
HL (mm) ca.	6.000

Abmessung d x s (mm)	Abwickl. (mm)	Gewicht (~kg/m)	
60 x 10,0	188,50	4,53	●
65 x 2,5	204,20	1,39	●
70 x 2,0	219,91	1,16	●
x 2,5	219,91	1,62	●
x 3,0	219,91	1,80	●
x 4,0	219,91	2,39	●
x 5,0	219,91	2,76	○
x 10,0	219,91	5,44	○
80 x 2,0	251,33	1,32	●
x 3,0	251,33	2,06	●
x 4,0	251,33	2,39	●
x 5,0	251,33	3,40	●
x 10,0	251,33	6,35	●
85 x 5,0	267,04	3,56	○
90 x 2,0	282,74	1,57	○
x 2,5	282,74	1,97	●
x 3,0	282,74	2,31	●
x 5,0	282,74	3,85	●
x 6,0	282,74	4,62	○
100 x 2,0	314,16	1,67	●
x 2,5	314,16	2,16	○
x 3,0	314,16	2,59	●
x 4,0	314,16	3,25	○
x 5,0	314,16	4,03	●
x 8,0	314,16	6,57	○
x 10,0	314,16	8,16	○
108 x 3,0	339,29	2,81	●
110 x 5,0	345,58	4,76	○
120 x 2,0	376,99	2,11	○
x 3,0	376,99	3,13	●
x 5,0	376,99	5,21	○
130 x 3,0	408,41	3,92	○
x 5,0	408,41	5,67	●
140 x 5,0	439,82	6,01	○
150 x 2,0	471,24	3,41	○
x 3,0	471,24	3,74	○
x 5,0	471,24	6,15	○
160 x 5,0	502,65	7,03	●
200 x 5,0	628,32	8,42	●

○ = kurzfristig lieferbar ● = auf Lager

Wir weisen darauf hin, dass sich die angegebenen Gewichte auf die spezifische Dichte von 2,7 g/cm³ beziehen!

